

POWERTRON 10W-40 SEMI-SYNTHETIC MOTOR OIL

TECHNICAL DATA SHEET

Product Description

Veedol Powertron 10W-40 is a high performance semi synthetic oil suitable for petrol and diesel engines including turbo, fuel injection and vehicles fitted with catalytic converters

Performance Specifications:

Veedol Powertron 10W-40 meets the following performance requirements:

API: SN/CFACEA: A3/B4MB: 229.3

VW: 502.00, 505.00
 Panault: PN0700/PNI

Renault: RN0700/RN0710

BMW: LL-01PSA: B71 2296Porsche: A40

Features/Benefits:

- Ensures lubricant performance
- · Excellent high & low temperature performance
- Outstanding fuel efficiency
- · Effective environmental protection







POWERTRON 10W-40 SEMI-SYNTHETIC MOTOR OIL

TECHNICAL DATA SHEET

Typical Properties

	ASTM Method	10W40
DENSITY @ 15°C	D 4052	0.86
KINEMATIC VISCOSITY CST @ 100°C	D 445	14.5
VISCOSITY INDEX	D 2270	165
FLASH POINT, °C	D 92	222
POUR POINT, °C	D 97	-34
TBN, mgKOH/g	D 2896	13

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

Health and Safety

Veedol Powertron Passenger Car Motor Oil is made with highly quality synthetic and mineral base oils, polymers and premium additives. As with any petroleum product, careful handling and good hygiene should be practised. Avoid prolonged skin exposure, splashing into eyes or ingestion. For more information, please consult our Material Safety Data Sheet (MSDS) which you can find at www.veedolamericas.com

