

POWERTRON 5W-30 SEMI-SYNTHETIC MOTOR OIL

TECHNICAL DATA SHEET

Product Description

Veedol Powertron 5W-30 is a semi synthetic high performance multigrade engine oil engineered with latest in lubricant technology providing excellent performance in tough conditions. Veedol Powertron's high quality blend and advanced technology delivers excellent fuel economy with improved film strength and oxidation stability. It is ideal for vehicles requiring 5W-30 viscosity engine oil including naturally aspirated and turbo charged units.

Performance Specifications:

Veedol Syntron 5W-30 meets the following performance requirements:

API: SN/CFACEA: A3/B4MB: 229.5BMW:LL-01

Renault: RN0700/RN0710

Features/Benefits:

- · Excellent fuel efficiency.
- Provides optimum performance and engine protection at extreme temperature.
- Excellent piston cleanliness.
- Protects against sludge formation and combustion contamination.







POWERTRON 5W-30 SEMI-SYNTHETIC MOTOR OIL

TECHNICAL DATA SHEET

Typical Properties

	ASTM Method	5W30
DENSITY @ 15°C	D 4052	0.852
KINEMATIC VISCOSITY CST @ 100°C	D 445	11.14
VISCOSITY INDEX	D 2270	157
FLASH POINT, °C	D 92	225
POUR POINT, °C	D 97	-43
TBN, mgKOH/g	D 2896	10.8

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

Health and Safety

Veedol Powertron Passenger Car Motor Oil is made with highly quality synthetic and mineral base oils, polymers and premium additives. As with any petroleum product, careful handling and good hygiene should be practised. Avoid prolonged skin exposure, splashing into eyes or ingestion. For more information, please consult our Material Safety Data Sheet (MSDS) which you can find at www.veedolamericas.com

