

POWERTRON UltraSYNTHETIC MOTOR OIL

TECHNICAL DATA SHEET

Product Description

Veedol Powertron Ultra 5W - 40 Synthetic engine oil is a premium quality synthetic passenger car engine oil developed according to today's technology and based on specially selected base oils that have a high natural viscosity index. With the addition of advanced additives, Powertron Ultra delivers a high level of engine protection while maintaining engine performance and longevity.

Performance Specifications:

Meets or exceeds API SN/CF and ACEA C3-12

OEM Approvals: MB-Approval 229.51, Approved under VW 502.00/505.00, BMW Longlife-04 (LL-04).

Meets the requirements of: MB 229.31/226.5, Ford M2C917-A, Porsche A40, Renault RN0700/RN0710, Dexos 2 Fiat 9.55535-S2.

Features/Benefits:

- High resistance against shearing
- Fast cold start
- Safe lubrication film at very high temperatures
- · Reduced formation of combustion ashes
- Very good detergency and dispersion
- · Very strong protection against wear, corrosion and foaming





POWERTRON Ultra SYNTHETIC MOTOR OIL

TECHNICAL DATA SHEET

Typical Properties

		ASTM Method	SAE 5W-40
Density		D 4052	0.850
Kinematic Viscosity			
	cSt @40°C	D 455	82.8
	cSt @100°C	D 455	14
Viscosity Index		D 2270	175
Flash Point, °C		D 92	232
Pour Point, °C		D97	-42
TBN		D 2896	7.4

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

Health and Safety

Veedol Powertron Ultra Synthetic Passenger Car Motor Oil is made with highly quality synthetic base oils, polymers and premium additives. As with any petroleum product, careful handling and good hygiene should be practiced. Avoid prolonged skin exposure, splashing into eyes or ingestion. For more information, please consult our Material Safety Data Sheet (MSDS) which you can find at www.asaveedol.com

